

---

**HIGH VOLTAGE CONVERTER FOR AN  
IMPLANTABLE MEDICAL DEVICE**

---

5

**Field of the Invention**

The present invention relates to implantable medical devices and, in particular, concerns a high voltage converter used in implantable medical devices that is configured to reduce loss of battery power due to leaking capacitors.

**Background of the Invention**

Implantable medical devices are devices that are implanted within the body of a patient so as to provide therapy to an organ of the patient. These types of devices have become increasingly common for the treatment of a variety of different medical ailments. For example, implantable cardiac stimulation devices, such as pacemakers and implantable cardioverter defibrillators (ICD's), have been in use for many years and provide electrical stimuli to the heart of the patient to regulate heart function. Similarly, neural stimulators are also now being implanted into patients' bodies in order to provide electrical stimulation to selected regions of the patient's brain to regulate brain function. Other medical devices can include devices for stimulating other organs or tissues, such as the pancreas, kidneys, etc.

Typically, an implantable medical device is equipped with a battery that supplies low voltage DC power to the implanted device. Generally, known low voltage batteries such as lithium, iodine, silver vanadium oxide (SVO) or lithium monofluoride batteries are used to provide power to the implantable device. Typically, these batteries provide output voltages in the range of 2 to 4 volts DC. However, it common for the implantable

medical device to provide comparatively high voltage waveforms to an organ of the patient in order to regulate the organ's function.

For example, ICD's will often provide waveforms having peak voltage of approximately 800 volts or greater to the heart of a patient in order to terminate ventricular fibrillation. Similarly, neural stimulators will provide voltages in the range of 20 to 50 volts in order to terminate epileptic episodes. Hence, many implantable medical devices are equipped with a high voltage converter that uses the relatively low output voltage provided by the battery to develop a high voltage output signal that can be applied to one or more high voltage capacitors. When the capacitor(s) voltage reaches a programmed value, the charge stops and next the capacitor(s) voltage is applied to the organ of the patient using specialized HV switching means.

A typical high voltage converter used in implantable medical devices generally has a primary winding of a transformer being connected to the positive and negative plates of a battery via a switch, such as a transistor. One or more bypass capacitors are connected in parallel to the battery such that the bypass capacitors help maintain the voltage supplied to the transformer primary at a stable level during charging. A high voltage rectification circuit that includes one or more delivery capacitors is typically connected to the secondary winding of the transformer. Moreover, a switching network is generally attached to the switch such that the switch can be toggled at relatively high frequency. When the switch is turned on, an increasing current is provided to the primary winding of the transformer which stores energy as magnetic flux in the core of the transformer. When the switch is turned off, the stored energy is transferred from the core to the load via the secondary winding. Hence, by repeatedly cycling the switch at a relatively high frequency, energy can be transferred from the battery to the high voltage capacitors.

To improve the efficiency of this high voltage charging process, the bypass capacitors that are used are typically capacitors that have particularly low equivalent series resistance. Lower equivalent series resistance among the capacitors results in less of the battery's energy being dissipated in the form of heat in the resistance. Of course, in implanted medical devices, conservation of battery power is important as replacement of the battery often requires an invasive surgical procedure.

One common family of capacitors that is used as bypass capacitors in high voltage converter circuits for implantable medical devices is ceramic dielectric capacitors with a Y5V dielectric. Advantageously, ceramic capacitors are known to have particularly low equivalent series resistance and, thus, increases the efficiency of converter circuits.

One problem with ceramic capacitors is that these types of capacitors are typically not self-healing. In other words, if cracks develop in the ceramic dielectric, leakage currents will then flow from one plate of the capacitor to the other. This leakage current also represents an unwanted dissipation of the battery's energy and discharge it in a relatively short period. Typically, with the electrolytic capacitors that are also commonly used in implantable medical devices, leakage paths that develop between the plates as a result of applied voltages are often repaired by the electrolyte. Consequently, electrolytic capacitors have reduced leakage currents after an internal defect but, unfortunately, they also have a higher equivalent series resistance.

Hence, while ceramic capacitors are generally preferred to be used as the bypass capacitors in high voltage converter circuits for implantable medical devices, these ceramic capacitors also may produce leakage paths through which battery power can be dissipated when the bypass capacitors are not being charged. Again, dissipation of battery power is undesirable due to the difficulties associated with replacing batteries in

implantable medical devices and also the consequences of battery failure in an implanted device. Hence, there is a need for a high voltage converter circuit for an implantable medical device that permits efficient charging of the HV capacitor but also reduces unwanted dissipation of battery power during the quiescent period of the high voltage converter circuit in an event of capacitors degradation. To this end, there is a need for a high voltage converter circuit for an implantable medical device with which high efficiency capacitors, such as ceramic capacitors, can be used as bypass capacitors while the effect of such leakage current that may occur with such types of capacitors can be reduced or eliminated.

### **Summary of the Invention**

The aforementioned needs are satisfied by the implantable medical device described herein which, in one aspect, comprises a device that delivers high voltage therapeutic stimulation to an organ of the patient. This device includes an implantable delivery device that delivers the therapeutic stimulation to the organ of the patient, a battery and a converter that is coupled to the battery and to the implantable delivery device. For the purpose of this description, a high voltage is defined as any voltage higher than the battery voltage. The converter includes at least one bypass capacitor that is selectively connected to the battery via a switching network and at least one delivery capacitor that is coupled to the implantable delivery circuit.

The device further includes a controller that induces the battery and the at least one bypass capacitor to be connected to the battery such that charge is accumulated in the bypass capacitor during a charging cycle and the controller further induces the at least one bypass capacitor and the battery to be periodically coupled to the delivery capacitor such that charge is accumulated in the delivery capacitor so as to develop a high voltage charge in the delivery capacitor for delivery of the high

voltage therapeutic stimulation to the organ of the patient. The controller is further configured to disconnect at least one bypass capacitor from the battery after completion of the charging cycle to inhibit undesired dissipation of battery energy as a result of leakage currents during quiescent periods of the converter.

In one particular implementation, the bypass capacitors are connected to a primary winding of a transformer in series with a first switching element, such as a transistor, and the bypass capacitors are also connected to the battery via a second switching element, such as a transistor and a shunt resistor intended to sense the transformer primary current. The controller induces the delivery of an alternating signal, such as a square wave signal, to the first switching element, such that the battery and the bypass capacitors are selectively connected and disconnected to the primary winding of the transformer. In this way, a varying current is applied to the primary winding which results in a varying current being inductively induced on the secondary winding to thereby charge the delivery capacitors.

The circuit is further configured so as to deliver a substantially constant output signal to the second switching element whenever the alternating signal is being provided to the first switching element. When the controller is no longer providing the alternating signal to the first switching element, the second switching element is disabled which thereby disconnects the bypass capacitors from the battery. In this way, unwanted dissipation of battery energy as a result of leakage across the plurality of bypass capacitors is eliminated. While the HV converter is working, and this is only for a few seconds at a time, the additional leakage current is insignificant compared with the high current required for conversion.

In one particular implementation, the implantable medical device comprises an implantable cardiac stimulation device, such as an

implantable cardioverter defibrillator (ICD). It will, of course, be appreciated, however, that the implantable medical device can comprise any of a number of implantable medical devices that need to apply an output voltage that is substantially greater than the voltage provided by the battery such that the output voltage must be developed using capacitors. The use of a circuit that selectively disconnects the bypass capacitors allows for the use of bypass capacitors, such as ceramic capacitors, which are more efficient due to their relatively low equivalent series resistance, but may otherwise generate leakage currents. These and other objects and advantages will become more apparent from the following description taken in conjunction with accompanying drawings.

#### **Brief Description of the Drawings**

Further features and advantages of the device described herein may be more readily understood by reference to the following description taken in conjunction with the accompanying drawings, in which:

**Fig. 1** is a simplified diagram illustrating an implantable stimulation device in electrical communication with at least three leads implanted into a patient's heart for delivering multi-chamber stimulation and shock therapy;

**Fig. 2** is a functional block diagram of a multi-chamber implantable stimulation device illustrating the basic elements of a stimulation device which can provide cardioversion, defibrillation and pacing stimulation in four chambers of the heart;

**Fig. 3** is a schematic diagram of a high voltage converter circuit that is part of the shocking circuit of **Fig. 2**; and

**Fig. 4** is an exemplary schematic of the high voltage discharge capacitor that is part of the shocking circuit of **Fig. 2**.

**Detailed Description of the Preferred Embodiment**

The following description is of the best mode presently contemplated. This description is not to be taken in a limiting sense but is made merely for the purpose of describing the general principles of the device. The scope of the invention should be ascertained with reference to the issued claims. In the description that follows, like numerals or reference designators will be used to refer to like parts or elements throughout.

As shown in Fig. 1, there is a stimulation device 10 in electrical communication with a patient's heart 12 by way of three leads, 20, 24 and 30, suitable for delivering multi-chamber stimulation and shock therapy. To sense atrial cardiac signals and to provide right atrial chamber stimulation therapy, the stimulation device 10 is coupled to an implantable right atrial lead 20 having at least an atrial tip electrode 22, which typically is implanted in the patient's right atrial appendage.

To sense left atrial and ventricular cardiac signals and to provide left chamber pacing therapy, the stimulation device 10 is coupled to a "coronary sinus" lead 24 designed for placement in the "coronary sinus region" via the coronary sinus os for positioning a distal electrode adjacent to the left ventricle and/or additional electrode(s) adjacent to the left atrium. As used herein, the phrase "coronary sinus region" refers to the vasculature of the left ventricle, including any portion of the coronary sinus, great cardiac vein, left marginal vein, left posterior ventricular vein, middle cardiac vein, and/or small cardiac vein or any other cardiac vein accessible by the coronary sinus.

Accordingly, an exemplary coronary sinus lead 24 is designed to receive atrial and ventricular cardiac signals and to deliver left ventricular pacing therapy using at least a left ventricular tip electrode 26, left atrial pacing therapy using at least a left atrial ring electrode 27, and shocking therapy using at least a left atrial coil electrode 28. For a complete

description of a coronary sinus lead, see U.S. Patent Application No. 09/457,277, "A Self-Anchoring, Steerable Coronary Sinus Lead" (Pianca et al.), and U.S. Patent No. 5,466,254, "Coronary Sinus Lead with Atrial Sensing Capability" (Helland), which patents are hereby incorporated  
5 herein by reference.

The stimulation device 10 is also shown in electrical communication with the patient's heart 12 by way of an implantable right ventricular lead 30 having, in this embodiment, a right ventricular tip electrode 32, a right ventricular ring electrode 34, a right ventricular (RV)  
10 coil electrode 36, and an SVC coil electrode 38. Typically, the right ventricular lead 30 is transvenously inserted into the heart 12 so as to place the right ventricular tip electrode 32 in the right ventricular apex so that the RV coil electrode will be positioned in the right ventricle and the SVC coil electrode 38 will be positioned in the superior vena cava.  
15 Accordingly, the right ventricular lead 30 is capable of receiving cardiac signals, and delivering stimulation in the form of pacing and shock therapy to the right ventricle.

As illustrated in Fig. 2, a simplified block diagram is shown of the multi-chamber implantable stimulation device 10, which is capable of  
20 treating both fast and slow arrhythmias with stimulation therapy, including cardioversion, defibrillation, and pacing stimulation. While a particular multi-chamber device is shown, this is for illustration purposes only, and one of skill in the art could readily duplicate, eliminate or disable the appropriate circuitry in any desired combination to provide a device  
25 capable of treating the appropriate chamber(s) with cardioversion, defibrillation and pacing stimulation.

The housing 40 for the stimulation device 10, shown schematically in Fig. 2, is often referred to as the "can", "case" or "case electrode" and may be programmably selected to act as the return electrode for all  
30 "unipolar" modes. The housing 40 may further be used as a return



electrode alone or in combination with one or more of the coil electrodes, 28, 36 and 38, for shocking purposes. The housing 40 further includes a connector (not shown) having a plurality of terminals, 42, 44, 46, 48, 52, 54, 56, and 58 (shown schematically and, for convenience, the names of the electrodes to which they are connected are shown next to the terminals). As such, to achieve right atrial sensing and pacing, the connector includes at least a right atrial tip terminal ( $A_R$  TIP) 42 adapted for connection to the atrial tip electrode 22.

To achieve left chamber sensing, pacing and shocking, the connector includes at least a left ventricular tip terminal ( $V_L$  TIP) 44, a left atrial ring terminal ( $A_L$  RING) 46, and a left atrial shocking terminal ( $A_L$  COIL) 48, which are adapted for connection to the left ventricular ring electrode 26, the left atrial tip electrode 27, and the left atrial coil electrode 28, respectively.

To support right chamber sensing, pacing and shocking, the connector further includes a right ventricular tip terminal ( $V_R$  TIP) 52, a right ventricular ring terminal ( $V_R$  RING) 54, a right ventricular shocking terminal ( $R_V$  COIL) 56, and an SVC shocking terminal (SVC COIL) 58, which are adapted for connection to the right ventricular tip electrode 32, right ventricular ring electrode 34, the RV coil electrode 36, and the SVC coil electrode 38, respectively.

At the core of the stimulation device 10 is a programmable microcontroller 60 which controls the various modes of stimulation therapy. As is well known in the art, the microcontroller 60 typically includes a microprocessor, or equivalent control circuitry, designed specifically for controlling the delivery of stimulation therapy and may further include RAM or ROM memory, logic and timing circuitry, state machine circuitry, and I/O circuitry. Typically, the microcontroller 60 includes the ability to process or monitor input signals (data) as controlled by a program code stored in a designated block of memory. The details

of the design and operation of the microcontroller 60 are not critical. Rather, any suitable microcontroller 60 may be used that carries out the functions described herein. The use of microprocessor-based control circuits for performing timing and data analysis functions are well known in the art.

As shown in Fig. 2, an atrial pulse generator 70 and a ventricular pulse generator 72 generate pacing stimulation pulses for delivery by the right atrial lead 20, the right ventricular lead 30, and/or the coronary sinus lead 24 via an electrode configuration switch 74. It is understood that in order to provide stimulation therapy in each of the four chambers of the heart, the atrial and ventricular pulse generators, 70 and 72, may include dedicated, independent pulse generators, multiplexed pulse generators, or shared pulse generators. The pulse generators, 70 and 72, are controlled by the microcontroller 60 via appropriate control signals, 76 and 78, respectively, to trigger or inhibit the stimulation pulses.

The microcontroller 60 further includes timing control circuitry 79 which is used to control the timing of such stimulation pulses (e.g., pacing rate, atrio-ventricular (AV) delay, atrial interconduction (A-A) delay, or ventricular interconduction (V-V) delay, etc.) as well as to keep track of the timing of refractory periods, PVARP intervals, noise detection windows, evoked response windows, alert intervals, marker channel timing, etc., which is well known in the art.

The switch 74 includes a plurality of switches for connecting the desired electrodes to the appropriate I/O circuits, thereby providing complete electrode programmability. Accordingly, the switch 74, in response to a control signal 80 from the microcontroller 60, determines the polarity of the stimulation pulses (e.g., unipolar, bipolar, combipolar, etc.) by selectively closing the appropriate combination of switches (not shown) as is known in the art.

Atrial sensing circuits 82 and ventricular sensing circuits 84 may also be selectively coupled to the right atrial lead 20, coronary sinus lead 24, and the right ventricular lead 30, through the switch 74 for detecting the presence of cardiac activity in each of the four chambers of the heart.

- 5 Accordingly, the atrial (ATR. SENSE) and ventricular (VTR. SENSE) sensing circuits, 82 and 84, may include dedicated sense amplifiers, multiplexed amplifiers, or shared amplifiers. The switch 74 determines the "sensing polarity" of the cardiac signal by selectively closing the appropriate switches, as is also known in the art. In this way, the clinician  
10 may program the sensing polarity independent of the stimulation polarity.

- Each sensing circuit, 82 and 84, preferably employs one or more low power, precision amplifiers with programmable gain and/or automatic gain control, bandpass filtering, and a threshold detection circuit, as known in the art, to selectively sense the cardiac signal of interest. The  
15 automatic gain control enables the device 10 to deal effectively with the difficult problem of sensing the low amplitude signal characteristics of atrial or ventricular fibrillation. The outputs of the atrial and ventricular sensing circuits, 82 and 84, are connected to the microcontroller 60 which, in turn, are able to trigger or inhibit the atrial and ventricular pulse  
20 generators, 70 and 72, respectively, in a demand fashion in response to the absence or presence of cardiac activity in the appropriate chambers of the heart.

- For arrhythmia detection, the device 10 utilizes the atrial and ventricular sensing circuits, 82 and 84, to sense cardiac signals to  
25 determine whether a rhythm is physiologic or pathologic. As used herein "sensing" is reserved for the noting of an electrical signal, and "detection" is the processing of these sensed signals and noting the presence of an arrhythmia. The timing intervals between sensed events (e.g., P-waves, R-waves, and depolarization signals associated with fibrillation which are  
30 sometimes referred to as "F-waves" or "Fib-waves") are then classified by

the microcontroller 60 by comparing them to a predefined rate zone limit (i.e., bradycardia, normal, low rate VT, high rate VT, and fibrillation rate zones) and various other characteristics (e.g., sudden onset, stability, physiologic sensors, and morphology, etc.) in order to determine the type of remedial therapy that is needed (e.g., bradycardia pacing, anti-tachycardia pacing, cardioversion shocks or defibrillation shocks, collectively referred to as "tiered therapy").

Cardiac signals are also applied to the inputs of an analog-to-digital (A/D) data acquisition system 90. The data acquisition system 90 is configured to acquire intracardiac electrogram signals, convert the raw analog data into a digital signal, and store the digital signals for later processing and/or telemetric transmission to an external device 102. The data acquisition system 90 is coupled to the right atrial lead 20, the coronary sinus lead 24, and the right ventricular lead 30 through the switch 74 to sample cardiac signals across any pair of desired electrodes.

The microcontroller 60 is further coupled to a memory 94 by a suitable data/address bus 96, wherein the programmable operating parameters used by the microcontroller 60 are stored and modified, as required, in order to customize the operation of the stimulation device 10 to suit the needs of a particular patient. Such operating parameters define, for example, pacing pulse amplitude, pulse duration, electrode polarity, rate, sensitivity, automatic features, arrhythmia detection criteria, and the amplitude, waveshape and vector of each shocking pulse to be delivered to the patient's heart 12 within each respective tier of therapy.

Advantageously, the operating parameters of the implantable device 10 may be non-invasively programmed into the memory 94 through a telemetry circuit 100 in telemetric communication with the external device 102, such as a programmer, transtelephonic transceiver, or a diagnostic system analyzer. The telemetry circuit 100 is activated by the microcontroller by a control signal 106. The telemetry circuit 100

advantageously allows intracardiac electrograms and status information relating to the operation of the device 10 (as contained in the microcontroller 60 or memory 94) to be sent to the external device 102 through an established communication link 104.

5 In the preferred embodiment, the stimulation device 10 further includes a physiologic sensor 108, commonly referred to as a "rate-responsive" sensor because it is typically used to adjust pacing stimulation rate according to the exercise state of the patient. However, the physiological sensor 108 may further be used to detect changes in  
10 cardiac output, changes in the physiological condition of the heart, or diurnal changes in activity (e.g., detecting sleep and wake states). Accordingly, the microcontroller 60 responds by adjusting the various pacing parameters (such as rate, AV Delay, V-V Delay, etc.) at which the atrial and ventricular pulse generators, 70 and 72, generate stimulation  
15 pulses.

The stimulation device additionally includes a battery 110 which provides operating power to all of the circuits shown in Fig. 2. For the stimulation device 10, which employs shocking therapy, the battery 110 must be capable of operating at low current drains for long periods of time  
20 and then be capable of providing high-current pulses (for capacitor charging) when the patient requires a shock pulse. The battery 110 must also have a predictable discharge characteristic so that elective replacement time can be detected. Accordingly, the device 10 preferably employs lithium/silver vanadium oxide batteries, as is true for most (if not  
25 all) current devices.

As further shown in Fig. 2, the device 10 is shown as having an impedance measuring circuit 112 which is enabled by the microcontroller 60 via a control signal 114.

30 In the case where the stimulation device 10 is intended to operate as an implantable cardioverter/ defibrillator (ICD) device, it must detect

the occurrence of an arrhythmia, and automatically apply an appropriate electrical shock therapy to the heart aimed at terminating the detected arrhythmia. To this end, the microcontroller 60 further controls a shocking circuit 116 by way of a control signal 118. The shocking circuit 116  
5 generates shocking pulses of low (up to 0.5 Joules), moderate (0.5 - 10 Joules), or high energy (11 to 40 Joules), as controlled by the microcontroller 60. Such shocking pulses are applied to the patient's heart 12 through at least two shocking electrodes, and as shown in this embodiment, selected from the left atrial coil electrode 28, the RV coil  
10 electrode 36, and/or the SVC coil electrode 38. As noted above, the housing 40 may act as an active electrode in combination with the RV electrode 36, or as part of a split electrical vector using the SVC coil electrode 38 or the left atrial coil electrode 28 (i.e., using the RV electrode as a common electrode).

15 Cardioversion shocks are generally considered to be of low to moderate energy level (so as to minimize pain felt by the patient), and/or synchronized with an R-wave and/or pertaining to the treatment of tachycardia. Defibrillation shocks are generally of moderate to high energy level (i.e., corresponding to thresholds in the range of 5-40  
20 Joules), delivered asynchronously (since R-waves may be too disorganized), and pertaining exclusively to the treatment of fibrillation. Accordingly, the microcontroller 60 is capable of controlling the synchronous or asynchronous delivery of the shocking pulses.

**Fig. 3** is a block diagram illustrating a high voltage converter circuit  
25 200 that, in this particular implementation, is part of the shocking circuit 116 of **Fig. 2**. As discussed above, the implantable cardiac stimulation device 10 includes the battery 110 that provides a low voltage output, e.g., on the order of 3 volts, and a shocking circuit 116 that provides a high voltage shock to the heart of the patient via the leads 20, 24, and 30.  
30 Consequently, the shocking circuit 116 must incorporate circuitry that will

develop a high voltage, e.g., on the order of 150-800 volts, signal using the output voltage of the battery 110. As is illustrated in **Fig. 3**, the high voltage converter circuit 200 in this particular implementation includes a plurality of bypass capacitors 210, denoted C1-C3, that are generally  
5 connected in parallel with the battery 110 through a primary switch element Q2 and a current sensing resistor R1. The plurality of bypass capacitors are preferably ceramic capacitors with a Y5V dielectric. Typically, the plurality of these capacitors have a capacitance on the order of 20 to 50 microfarad. As is also illustrated in **Fig. 3**, the plurality  
10 of bypass capacitors 210 are connected across the primary winding 212a of a transformer 212 in series with a secondary switch element Q1, such that pulsed current drawn by the transformer 212 does not result in too high a voltage ripple on the battery voltage. Moreover, the primary winding of the transformer 212a is connected to the positive side of the  
15 battery 110 via a sensing resistor 230 denoted R1 in **Fig. 3**. The primary winding 212a is also connected to the negative side of the battery 110 via a transistor 232, denoted Q1 in **Fig. 3**, and a transistor 234, denoted Q2 in **Fig. 3**.

The secondary winding 212b of the transformer 212 is then  
20 coupled to a high voltage rectification circuit 214 that will be described in greater detail in connection with **Fig. 4**. The gate of the transistor 232 is connected to a gate drive circuit 216 which is controlled by the programmable microcontroller 60 in the manner that will be described in greater detail below. Moreover, the gate of the transistor 234 is also  
25 connected to the output of the gate drive circuits 216 via a diode 240. As will be discussed below, the gate of the second transistor 234 can also be connected to the negative side of the battery 110 via an optional resistor 242.

As is also illustrated in **Fig. 3**, the sensing resistor 230 is preferably  
30 connected to a current sensing logic circuit 218 that is also controlled by

the programmable microcontroller 60. As is understood, the current sensing circuit 218 samples the voltage at the resistor 230 in order to further regulate the charge current that is being supplied to the primary winding 212a of the transformer 212.

- 5        These components shown in **Fig. 3** comprise the basic high voltage converter circuit 200 of the preferred embodiment. As is further illustrated in **Fig. 3**, the rest of the device circuitry 224 discussed above in connection with **Figs. 1** and **2**, also receive power from the positive and negative sides of the battery 110 in a manner that is known in the art.
- 10      Moreover, as is illustrated in **Fig. 3**, a decoupling capacitor 220, which in this embodiment comprises an electrolytic capacitor having a capacitance on the order of 10-30 microfarads is connected in parallel to the battery 110 such that a substantially low voltage ripple DC voltage can be provided to the rest of the device circuitry 224 without being substantially
- 15      affected by the operation of the high voltage converter circuit 200.

- The high voltage converter 200 is endeavoring to charge one or more delivery capacitors to a relatively high level of voltage such that the delivery capacitors can then provide a high voltage output waveform to the patient's body in the above-described manner. In order to charge the
- 20      high voltage delivery capacitors, the programmable microcontroller 60, via the gate drive circuit 216, provides a high frequency square wave signal to the gate of the transistor 232. As a result of the diode 240 and the intrinsic transistor 234 gate-source capacitance, the high frequency square wave signal that is being provided to the gate of the transistor 232
- 25      is rectified into a positive output voltage on the transistor 234 gate. Consequently, the transistor 234 is then turned continuously on, but the transistor 232 is turned on and off at a high frequency, e.g., on the order of 50 to 250 kHz.

- Hence, when the charging cycle is initiated, e.g., the high
- 30      frequency signal and the constant signal are being provided to the



transistors 232, 234 respectively, the bypass capacitors 210 are continuously connected to the battery 110 and can therefore provide a reservoir of charge to the transformer 212 during charging of the primary winding.

5 Charge is transferred to the HV rectification circuit 214 across the windings 212b in the following manner. When the high frequency signal to the transistor 232 is high, the winding 212a is connected across both the battery and the bypass capacitors 210 and receives charge from both these sources. This results in a changing current in the primary winding  
10 212a. When transistor 232 is controlled off, the stored energy in the transformer generates a secondary current in the secondary winding 212b. The current in the secondary winding is rectified by the HV rectification circuit 214 and charges delivery capacitors in a manner that will be described in greater detail hereinbelow. These on off cycles  
15 repeat at high frequency until the controller determines that the voltage on 220 is equal to the program voltage, when it stops driving the transistor 232 on and leaving it with a gate voltage close to zero. After converter is in this way turned off, the gate voltage on the transistor 234 slowly discharges to zero through the reverse leakage of Shottky diode  
20 240. After a second or so, the 234 gate voltage reaches zero and 234 switches off separating the bypass capacitors 210 from the battery. A resistor 242 of 10 Mohm can provide additional leakage to speed up this process if required.

As discussed above, the bypass capacitors 210 are preferably  
25 ceramic capacitors with Y5V dielectric and as explained earlier they can become leaky. However, as is shown in **Fig. 3**, the gate drive circuit 216 only connects the bottom plate of the bypass capacitors 210 to the negative pole of the battery 110 when the high frequency signal is being applied to the transistor 232. Hence, the bypass capacitors 210 are only  
30 connected to the battery 110 when the HV converter is actually operating,

i.e., the high frequency switching signal is being provided to the transistor 232. In this way, battery power is inhibited from leaking across the plates of the bypass capacitors during quiescent periods of the converter circuit.

More specifically, when the microcontroller 60 disables the gate drive 216 such that it is no longer providing the high frequency signal to the transistor 232, the voltage being applied to the gate of the transistor 234 goes low thereby creating a substantially open circuit between the bottom plates of the bypass capacitors 210 and the negative pole of the battery 110 which thereby inhibits undesirable leakage of the battery 110.

As is further illustrated in **Fig. 3**, an optional resistor 242 can also be interposed between the gate of the transistor 232 and the negative pole of the battery 110 such that, when the gate drive circuit 216 stops producing the high frequency square wave signal, the voltage on the gate of the transistor 234 can be pulled low, thereby hastening the turning off of the transistor 234 and the disconnecting of the bypass capacitors 210 from the battery 110.

**Fig. 4** is a simplified schematic illustrating the high voltage rectification circuit 214. As is illustrated, the secondary winding 212b is connected to delivery capacitors 240a, 240b via rectifying diodes 242a, 242b using a well known rectification circuit.

The delivery capacitors 240a, 240b, receive charge via the secondary winding 212b and build up sufficient charge that a high voltage waveform can be delivered. In some implementations, the storage capacitors 240a, 240b are capable of delivering a waveform having a voltage in excess of 800 volts.

While the device has been described in connection with a particular embodiment associated with an implantable cardiac stimulation device, it will be appreciated that any implantable medical device that requires the development of high voltage signals can use the high voltage converter circuit of the illustrated embodiment. For example, the

converter can also be used in an implantable medical device such as a neural stimulator like the stimulator disclosed in U.S. Patent No. 5,941,906 which is hereby incorporated by reference in its entirety.

- 5       Hence, although the foregoing description of the preferred  
embodiments has shown, described and pointed out the fundamental  
novel features of the device, it will be understood that various omissions,  
substitutions, and changes in the form of the detail of the apparatus as  
illustrated as well as the uses thereof, may be made by those skilled in  
the art without departing from the spirit of the present invention.
- 10       Consequently, the scope of the invention should not be limited to the  
foregoing discussion, but should be defined by the appended claims.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
219